



Full black electrophoresis process Looks nice and rich textured



Two kinds of cabinet versions: straight andcurved



Cabinet locks are precision and strongresistance, made by high-strength metal material





Front and rear maintenance of the module. Smps cover buckle lock design, make it tool free







Lighter than the big cabinet size of LS series, looks smart and compact










Hanging Lock/Locating Pin Make the installation more safe and high efficiency.

The Back Cover With Buckle Lock Installation and removal without tools, maintenance more convenient and high efficiency.



Side Lock (Straight Cabinet) Easy to assembly the cabinet, and make the screen seamless.






LM series has two kinds of cabinet versions, straight and curved cabinet.






Actual ground support system may differ from image 0°-15°














LM5.95(Outdoor)

LM8.33(Outdoor)

LM15.62(Outdoor)



Lifetime

Storage Temp/Humidity

X 8Pcs

Pixel Pitch	3.91mm	4.81mm	3.91mm	4.81mm	5.95mm	8.33mm	15.62mm
LED	SMD2020(Black)	SMD2020(Black)	SMD1921(High frame)	SMD1921(High frame	SMD1921(High frame)	SMD3535	SMD3535
Pixel Density	65536pixel/m²	43264pixel/m	65536pixel/m²	43264pixel/m²	28224pixel/m²	14400pixel/m	4096pixel/m²
Brightness	800-1100nits	800-1100nits	2000-2500nits 4000-4500nits	2000-2500nits 4000-4500nits	2200-2500nits 4000-4500nits	5000-5500nits	5000-5500nits
Color Temperature	6500-9500K						
Scan	1/16	1/13	1/16	1/13	1/7	1/3	Static
Panel Dimension(W*H*D)	500X500X75mm/19.7"X19.7"X3.0"						
Panel Resolution	128X128pixel	104X104pixel	128X128pixel	104X104pixel	84X84pixel	60X60pixel	32X32pixel
Panel Weight	8.00kg/17.64lb	8.00kg/17.64lb	8.50kg/18.74lb	8.50kg/18.74lb	8.50kg/18.74lb	8.50kg/18.74lb	8.50kg/18.74lb
Cabinet Material	Die casting aluminum						
Max Power Consumption	≤650w/m²	≤650w/m²	≤700w/m²	≤700w/m²	≤700w/m²	≤700w/m²	≤700w/m²
Average Power Consumption	≤325w/m²	≤325w/m²	≤350w/m²	≤350w/m²	≤350w/m²	≤350w/m²	≤350w/m²
Viewing Angle	H:160° V:140°	H:160° V:140°	H:140° V:120°	H:140° V:120°	H:140° V:120°	H:140° V:120°	H:140° V:120°
Refresh Rate	1920Hz						
Gray Scale	14-16bit						
IP Rating	IP30	IP30	Front IP65,Rear IP54	Front IP65,Rear IP54	Front IP65,Rear IP54	Front IP65,Rear IP54	Front IP65,Rear IP54
Operating Humidity	10%-60%RH	10%-60%RH	10%-90%RH	10%-90%RH	10%-90%RH	10%-90%RH	10%-90%RH
Operating Temperature	-20°C~+45°C						
Max. Stacking	20pcs						
Max. Hanging	20pcs						
Curve(Optional)	-7.5°~+7.5°						

LM4.81(Outdoor)

50,000hrs

-40°C~+60°C;10%-60%RH